

SPECIAL FEATURES: SPECIFICATIONS:

- Impregnated with an antimicrobial additive and treated to prevent or inhibit the growth of microorganisms which cause skin diseases such as Tinea and Athletes Foot.
- Designed as an interlocking roll-up mat system making its removal for cleaning easy. It can also be laid in a variety of patterns and can easily be installed by the end user.
- Free draining, to enable greater ease of cleaning with hoses, flush systems, vacuuming or steam cleaning.
- Manufactured from 100% recycled materials.
- Guaranteed for five years

Reg. Design 27249NZ

Dimensions: 500mm (20") long x 250mm (10") wide

x 15mm (9/16") high.


Weight: 700 grams (24oz) each. Material: Rubber and flexible P.V.C.

Load Capacity: 1050kg (2320 lbs) laid on a rigid base. **Colours:** White, black, green, red, blue, yellow and

grey.

Temperature: Suitable for use in temperatures ranging from -30°C (-22°F) to +90°C (194°F). Mat size increases up to 2mm (1/16") in length in temperatures up to 90°C (194°F).

Packaging: Packed in boxes of 20 with the box size being 515mm (20 3/8") long x 515mm (20 3/8") wide x 150mm (6") high. A full 20ft container holds approximately 14,600 mats.



When the mat edge is subject to foot traffic, additional safety is provided by the use of edge ramps.

Edge Ramp Specifications

Length of mitred ramp 560mm (22") x 60mm (2") Length of straight ramp 500mm (20") x 60mm (2") Tapered from 2mm (¹/16") - 15mm (⁹/16") over the width Weight 225 grams (8 oz.)



Easy to roll



Protection when you need it most!